


# AD 630

Doosan  
Mecc Alte  
D+ &



<b>ISO8528</b>	GC, ) &
<b>SZUTEST</b>	GC - \$\$\$
<b>CE</b>	

<b>2000/14/EC</b>	&\$\$\$#( #
	z) \$' z' \$z' D:

	"	kw	"	kw	Amp
400/230	630,00	504,00	575,00	460,00	830,00

	fP GDE	GC, ) &	
	fDF DE	GC" \$(**	z&(

### Standard Specifications

	z		
	fi	E	
	z		
	z		

### 1


### ALTERNATOR

	D; A Ž 5J F		

### 1


### TRANSFER SWITCH


# AD 630

Doosan  
Mecc Alte  
D+' &'

Manufacturer		Doosan		
Model		DP180LA		
		%\$\$' "# "		
		552,00 kw [740,00HP]		
	L	18,273		
	"	128 x 142		
		15,0:1		
	fl # ȷ	"# "	1500	
	fl ȷ	L	34,00	
		L	112,20	
AbsorbedAirDischargeReSourceKey.Text	' # "	33,20		
	' # "	700,00		
	' # "	106,00		
	° C	562,00		
		24 V d.c.		
	Load	%\$\$i	'+) i	) \$i
	# "	123,60	94,20	64,80

		Mecc Alte		
		ECO 40-1,5L/4		
	Hz	50		
	"	620,00		
7cg'		0,80		
		3		
	fl ȷ	400/230		
	A	894,90		

		fl ȷ		fl ȷ	
	"	"	"	"	L
AD 630		3264,00	1550,00	2056,00	850,00
		fl ȷ		fl ȷ	
	"	"	"	"	L
MS 80	4835	4810	1606	2615	850



# AD 630

Doosan  
Mecc Alte  
D+' &''

f@z@Bl  
f@z@Bl

"z" "z"

f@z@Bl

971

#

#

#

#

#

6G'9B'\*\$-\$)'\$

6G'9B'\*\$\$\$!\*!&

6G'9B'\*\$\$\$!\*!(

f&%) +L

f&)(, L

f&% \$L

GA 8

!&+""

)  
&(\$)

ž

ž

ž

ž

%, !&\*(

"

"

"

"

# AD 630

Doosan  
Mecc Alte  
D+ &''



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1606
fl "L	"	4810
fl "L	"	2615
	L	850